


'BLACK PIN'® CLEVIS GRAB HOOKS - ALLOY STEEL

- For use with Grade 70 or lower grade chains only
- Gold Chromate body with 'black pin'
- Design Factor 4:1

Size	WLL (lbs)	Dimensions (inches)				Weight (lbs)	Vanguard Code
		A	B	C	D		
1/4	3,150	0.36	0.38	0.39	1.97	0.46	3931 0016
5/16	4,700	0.38	0.44	0.43	2.28	0.75	3931 0020
3/8	6,600	0.47	0.47	0.50	2.61	1.10	3931 0024
7/16	8,800	0.67	0.55	0.58	2.79	1.53	3931 0028
1/2	11,300	0.76	0.62	0.67	3.13	2.34	3931 0032




NOT FOR LIFTING

'BLACK PIN'® CLEVIS SLIP HOOKS - ALLOY STEEL

- For use with Grade 70 or lower grade chains only
- Gold Chromate body with 'black pin'
- Design Factor 4:1
- Available with or without latches

Size	WLL (lbs)	Dimensions (inches)				Weight (lbs)	
		A	B	C	D		
1/4	2,750	0.43	0.38	0.98	2.52	0.65	
5/16	4,300	0.51	0.43	1.10	2.82	0.92	
3/8	5,250	0.58	0.47	1.33	3.22	1.32	
7/16	7,000	0.67	0.54	1.61	3.69	2.07	
1/2	9,000	0.76	0.62	1.74	3.99	2.90	



When ordering, please specify when hook with latch kit is required

NOT FOR LIFTING

Warning:

- **NEVER EXCEED WORKING LOAD LIMITS!**
- **NEVER** use grades lower than 80 for overhead lifting applications
- **ALWAYS** discard hooks, chain and other fittings which show signs of deformation or excessive wear or anything that would create doubt to the integrity of the product!

LOAD BINDER LOCKS

Load binder locks are designed to fit over load binder handles, locking into place with the aid of the steel spring clip. The U-shaped bracket fits over either the transport chain or the load binder handle.

The steel spring clip allows for the operator to either clip through the transport chain, around the load binder handle or through the hole found on most load binder handle and then around the transport chain

