



- YOKE alloy swivel hoist hook are manufactured from the finest quality alloy steel.
- YOKE swivel hoist hook are quenched and tempered.
- 20,000 cycle fatigue rated to 1.5 times of 4:1 WLL, Hook Code AA and KK to 1.5 times of 5:1 WLL.
- All swivel hoist hooks are 100% magnaflux crack detected.
- All parts with batch number for quality certified and traceability.
- YOKE Swivel Hoist Hooks are proof tested to 2.5 times of 4:1 WLL. Hook Code AA and KK to 2 times of 5:1 WLL.
- YOKE Swivel Hoist Hooks are Predrilled to accept a YOKE latch kits.

| Item No. | Working Load Limit | G100 Working Load Limit | Hook Feature Code | Dimensions (inch) | | | | | | | | | | | N.W. lbs | |
|-------------|--------------------|-------------------------|-------------------|-------------------|------|------|------|-------|------|-------|-------|------|------|------|-------------|--|
| | | | | A | B | C | D | G | H | K | L | P | P1 | T | | |
| with latch | tonnes* | | | | | | | | | | | | | | | |
| | 5 : 1 | 4 : 1 | | | | | | | | | | | | | | |
| 100SWBL1T | 1 | - | AA | 1.26 | 0.91 | 0.97 | 0.45 | 3.06 | 0.75 | 4.86 | 6.06 | 1.02 | 0.87 | 0.63 | 1.3 | |
| 100SWBL112T | 1.5 | 1.4 | BB | 1.26 | 0.91 | 0.97 | 0.45 | 3.15 | 0.84 | 4.96 | 6.23 | 0.95 | 0.75 | 0.71 | 1.5 | |
| 100SWBL2T | 2 | 2.5 | CC | 1.42 | 1.14 | 1.03 | 0.49 | 3.66 | 1.00 | 5.63 | 7.15 | 1.06 | 0.79 | 0.88 | 2.2 | |
| 100SWBL3T | 3 | 4 | DD | 1.62 | 1.38 | 1.16 | 0.63 | 4.02 | 1.13 | 7.73 | 8.36 | 1.22 | 0.98 | 0.95 | 3.5 | |
| 100SWBL5T | 5 | 6.7 | EE | 1.83 | 1.73 | 1.53 | 0.83 | 5.14 | 1.41 | 8.32 | 10.58 | 1.42 | 1.22 | 1.22 | 7.3 | |
| 100SWBL7T | 7 | 10 | FF | 2.40 | 1.99 | 1.94 | 0.89 | 6.60 | 1.82 | 10.18 | 12.92 | 1.77 | 1.54 | 1.42 | 12.3 | |
| 100SWBL11T | 11 | 16 | GG | 2.92 | 3.25 | 2.46 | 0.99 | 7.72 | 2.28 | 12.84 | 16.11 | 2.40 | 2.24 | 1.89 | 20.9 | |
| 100SWBL15T | 15 | 19 | HH | 3.83 | 3.78 | 2.59 | 1.30 | 8.70 | 2.53 | 14.64 | 18.55 | 2.83 | 2.44 | 2.20 | 35.2 | |
| 100SWBL22T | 22 | 26.5 | JJ | 4.83 | 4.55 | 2.81 | 2.01 | 10.91 | 3.00 | 18.42 | 23.58 | 3.39 | 3.19 | 2.69 | 73.7 | |
| 100SWBL30T | 30 | - | KK | 4.83 | 4.24 | 3.44 | 2.01 | 13.90 | 3.60 | 19.67 | 25.63 | 3.50 | 3.27 | 3.00 | 99.0 | |

- ★ Hook Code BB to JJ also categorized as G100 components.
- ★ Hook Code BB to JJ proof tested to 2.5 times of 4:1 WLL as G100 components.
- ★ Hook Code AA and KK proof tested to 2 times of 5:1 WLL.

| Item No. | Working Load Limit | G100 Working Load Limit | Hook Feature Code | Dimensions (mm) | | | | | | | | | | | N.W. kg |
|-------------|--------------------|-------------------------|-------------------|-----------------|-----|----|----|-----|----|-----|-----|----|----|----|------------|
| | | | | A | B | C | D | G | H | K | L | P | P1 | T | |
| with latch | tonnes* | | | | | | | | | | | | | | |
| | 5 : 1 | 4 : 1 | | | | | | | | | | | | | |
| 100SWBL1T | 1 | - | AA | 32 | 23 | 25 | 12 | 78 | 19 | 123 | 154 | 26 | 22 | 16 | 0.6 |
| 100SWBL112T | 1.5 | 1.4 | BB | 32 | 23 | 25 | 12 | 80 | 21 | 126 | 158 | 24 | 19 | 18 | 0.7 |
| 100SWBL2T | 2 | 2.5 | CC | 36 | 29 | 26 | 13 | 91 | 25 | 143 | 181 | 27 | 20 | 22 | 1.0 |
| 100SWBL3T | 3 | 4 | DD | 41 | 35 | 29 | 16 | 102 | 29 | 196 | 212 | 31 | 25 | 24 | 1.6 |
| 100SWBL5T | 5 | 6.7 | EE | 46 | 44 | 38 | 21 | 130 | 36 | 211 | 269 | 36 | 31 | 31 | 3.3 |
| 100SWBL7T | 7 | 10 | FF | 61 | 51 | 49 | 23 | 166 | 46 | 258 | 328 | 45 | 39 | 42 | 5.6 |
| 100SWBL11T | 11 | 16 | GG | 74 | 82 | 62 | 25 | 196 | 58 | 326 | 409 | 61 | 57 | 48 | 9.5 |
| 100SWBL15T | 15 | 19 | HH | 97 | 96 | 65 | 33 | 221 | 64 | 372 | 471 | 72 | 62 | 56 | 16.0 |
| 100SWBL22T | 22 | 26.5 | JJ | 123 | 116 | 71 | 51 | 277 | 76 | 469 | 599 | 86 | 81 | 68 | 33.5 |
| 100SWBL30T | 30 | - | KK | 123 | 116 | 87 | 51 | 353 | 93 | 503 | 651 | 89 | 83 | 76 | 45.0 |

- ★ Hook Code BB to JJ also categorized as G100 components.
- ★ Hook Code BB to JJ proof tested to 2.5 times of 4:1 WLL as G100 components.
- ★ Hook Code AA and KK proof tested to 2 times of 5:1 WLL.

