



- YOKE alloy swivel hoist hook are manufactured from the finest quality alloy steel.
- YOKE swivel hoist hook are quenched and tempered.
- 20,000 cycle fatigue rated to 1.5 times of 4:1 WLL, Hook Code AA and KK to 1.5 times of 5:1 WLL.
- All swivel hoist hooks are 100% magnaflux crack detected.
- All parts with batch number for quality certified and traceability.
- YOKE Swivel Hoist Hooks are proof tested to 2.5 times of 4:1 WLL. Hook Code AA and KK to 2 times of 5:1 WLL.
- YOKE Swivel Hoist Hooks are Predrilled to accept a YOKE latch kits.

Item No. with latch	Working Load Limit tonnes*	G100 Working Load Limit 4 : 1	Hook Feature Code	Dimensions (inch)											N.W. lbs	
				A	B		D	G	H	K	L	P	P1	T		
	5 : 1	4 : 1														
100SWL1T	1	-	AA	1.26	0.91	0.97	0.45	3.06	0.75	4.86	6.06	1.02	0.87	0.63	1.3	
100SWL112T	1.5	1.4	BB	1.26	0.91	0.97	0.45	3.15	0.84	4.96	6.23	0.95	0.75	0.71	1.5	
100SWL2T	2	2.5	CC	1.42	1.14	1.03	0.49	3.66	1.00	5.63	7.15	1.06	0.79	0.88	2.2	
100SWL3T	3	4	DD	1.62	1.38	1.16	0.63	4.02	1.13	7.73	8.36	1.22	0.98	0.95	3.3	
100SWL5T	5	6.7	EE	1.83	1.73	1.53	0.83	5.14	1.41	8.32	10.58	1.42	1.22	1.22	7.0	
100SWL7T	7	10	FF	2.40	1.99	1.94	0.89	6.60	1.82	10.18	12.92	1.77	1.54	1.42	12.5	
100SWL11T	11	16	GG	2.92	3.25	2.46	0.99	7.72	2.28	12.84	16.11	2.40	2.24	1.89	20.9	
100SWL15T	15	19	HH	3.83	3.78	2.59	1.30	8.70	2.53	14.64	18.55	2.83	2.44	2.20	36.3	
100SWL22T	22	26.5	JJ	4.83	4.55	2.81	1.64	10.91	3.00	18.42	23.58	3.39	3.19	2.69	73.5	
100SWL30T	30	-	KK	4.83	4.24	3.44	1.64	13.90	3.60	19.67	25.63	3.50	3.27	3.00	101.0	

- ★ Hook Code BB to JJ also categorized as G100 components.
- ★ Hook Code BB to JJ proof tested to 2.5 times of 4:1 WLL as G100 components.
- ★ Hook Code AA and KK proof tested to 2 times of 5:1 WLL.

Item No. with latch	Working Load Limit tonnes*	G100 Working Load Limit 4 : 1	Hook Feature Code	Dimensions (mm)											N.W. kg	
				A	B		D	G	H	K	L	P	P1	T		
	5 : 1	4 : 1														
100SWL1T	1	-	AA	32	23	25	12	78	19	123	154	26	22	16	0.6	
100SWL112	1.5	1.4	BB	32	23	25	12	80	21	126	158	24	19	18	0.7	
100SWL2T	2	2.5	CC	36	29	26	13	91	25	143	181	27	20	22	1.0	
100SWL3T	3	4	DD	41	35	29	16	102	29	196	212	31	25	24	1.5	
100SWL5T	5	6.7	EE	46	44	38	21	130	36	211	269	36	31	31	3.2	
100SWL7T	7	10	FF	61	51	49	23	166	46	258	328	45	39	42	5.7	
100SWL11T	11	16	GG	74	82	62	25	196	58	326	409	61	57	48	9.5	
100SWL15T	15	19	HH	97	96	65	33	221	64	372	471	72	62	56	16.5	
100SWL22T	22	26.5	JJ	123	116	71	51	277	76	469	599	86	81	68	33.4	
100SWL30T	30	-	KK	123	116	87	51	353	93	503	651	89	83	76	45.9	

- ★ Hook Code BB to JJ also categorized as G100 components.
- ★ Hook Code BB to JJ proof tested to 2.5 times of 4:1 WLL as G100 components.
- ★ Hook Code AA and KK proof tested to 2 times of 5:1 WLL.



Industrial Rigging & Supply