



**Application** : High pressure air service for mining, construction and industrial use. More resistant to external abuse than textile air hose. Mandrel built

**Cover** : Yellow cut and abrasion resistant rubber with red stripe

**Reinforcement** : Multiple layers of high tensile steel cords

**Tube** : Synthetic oil mist resistant

**Temperature** : -35C to +80C(-30F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1/2"	0.98"	1000	0.37	50'	SFY-050-50
1/2"	0.98"	1000	0.37	100'	SFY-050-100
3/4"	1.26"	800	0.49	50'	SFY-075-50
3/4"	1.26"	800	0.49	100'	SFY-075-100
1"	1.50"	800	0.66	50'	SFY-100-50
1"	1.50"	800	0.66	100'	SFY-100-100
1-1/4"	1.77"	600	0.80	50'	SFY-125-50
1-1/4"	1.77"	600	0.80	100'	SFY-125-100
1-1/2"	2.09"	600	1.03	50'	SFY-150-50
1-1/2"	2.09"	600	1.03	100'	SFY-150-100
2"	2.60"	600	1.51	50'	SFY-200-50
2"	2.60"	600	1.51	100'	SFY-200-100
2-1/2"	3.15"	500	2.12	100'	SFY-250
3"	3.82"	500	3.06	50'	SFY-300-50
3"	3.82"	500	3.06	100'	SFY-300-100
4"	4.84"	400	4.07	100'	SFY-400

**Cut Lengths** : Plus 10%, No cut lengths on 4".

**Standard Lengths** : 50'/100'

**Recommended Couplings** : High Pressure all sizes, mine stem and nut 1/2" - 2", Universal quick acting 1/2" - 1"

## HD Water Discharge/Low Pressure Air



**Application** : A heavy duty hose for water discharge, and light duty air service up to 100 psi for sizes up to 2 only.

**Cover** : Green abrasion and weather resistant synthetic rubber.

**Reinforcement** : Multiple layers of synthetic yarn.

**Tube** : Black synthetic rubber compounded for water service.

**Temperature** : -35C to +80C(-30F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1-1/4"	1.65"	150	0.61	100'	HDWG-125
1-1/2"	1.95"	150	0.79	100'	HDWG-150
2"	2.52"	150	1.25	100'	HDWG-200
2-1/2"	2.99"	150	1.44	100'	HDWG-250
3"	3.50"	125	1.78	100'	HDWG-300
4"	4.50"	125	2.51	100'	HDWG-400
5"	5.50"	125	2.40	100'	HDWG-500
6"	6.49"	125	4.29	100'	HDWG-600
8"	8.58"	125	5.06	100'	HDWG-800
10"	10.67"	125	6.27	50'	HDWG-1000
12"	12.67"	100	6.30	50'	HDWG-1200

**Cut Lengths** : Plus 10%

**Standard Lengths** : 50'/100'

**Recommended Couplings** : Cam and groove or short shank



**Industrial Rigging & Supply**