

Application : Heavy duty layflat hose for portable pump and irrigation use. : Green
Cover PVC impregnation.
Reinforcement : Woven high tensile synthetic yarns.
Tube : Green heavy PVC impregnation.
Temperature : -10C to +60C(15F to +140F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty
1-1/2"	1.75"	85	0.17	300'
2"	2.13"	80	0.23	300'
3"	3.13"	75	0.38	300'
4"	4.14"	75	0.53	300'
6"	6.28"	60	1.00	300'

Cut Lengths : Plus 10%

Standard Lengths : Multiples of 50' up to 300' maximum

Recommended Couplings : Cam and groove or short shank

Blue Layflat Hose



BUCHANAN RUBBER LTD.

Application : A light duty layflat hose for portable pump and irrigation use. : Blue
Cover PVC impregnation.
Reinforcement : Woven high tensile synthetic yarns.
Tube : Blue PVC impregnation.
Temperature : -10C to +55C(15F to +130F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty
3/4"	0.95"	150	0.11	300'
1"	1.11"	150	0.13	300'
1-1/4"	1.37"	130	0.15	300'
1-1/2"	1.63"	70	0.15	300'
2"	2.13"	65	0.20	300'
2-1/2"	2.63"	65	0.27	300'
3"	3.13"	60	0.33	300'
4"	4.14"	60	0.46	300'
5"	5.15"	45	0.65	300'
6"	6.15"	35	0.78	300'
8"	8.16"	35	1.22	300'
10"	10.20"	35	1.75	300'
12"	12.30"	30	2.50	300'

Cut Lengths : Plus 10%

Standard Lengths : Multiples of 50' up to 300' maximum

Recommended Couplings : Cam and groove or short shank



Industrial Rigging & Supply