

Application : Heavy duty layflat hose for portable pump and irrigation use.
Cover : Brown PVC impregnation.
Reinforcement : Woven high tensile synthetic yarns.
Tube : Brown heavy PVC impregnation.
Temperature : -10C to +60C(15F to +140F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty
1-1/2"	1.66"	130	0.20	300'
2"	2.16"	115	0.28	300'
3"	3.18"	100	0.46	300'
4"	4.18"	90	0.68	300'
6"	6.18"	70	1.10	300'
8"	8.19"	60	1.66	300'

Cut Lengths : Plus 10%


Standard Lengths : Multiples of 50' up to 300' maximum

Recommended Couplings : Cam and groove or short shank

Aztec Slurry Hose



BUCHANAN RUBBER LTD.



Application : Primarily designed for handling abrasive slurries in mines and quarries. Can also be used for dry material handling of sand, gravel, grain, slag, and other such materials. External re-usable bolt on flanges allow for ease of installation, and uninterrupted free flow.

Cover : Thick black corrugated abrasion and weather resistant synthetic blend. Specially compounded to stand up to heavy abuse in mines and quarries.

Reinforcement : Multiple layers of high tensile synthetic cords enveloping an extra heavy duty wire helix.

Tube : Ultra high quality blended rubber tube; 3/8" thick red tube.

Temperature : -40C to +80C(-40F to +180F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty
3"	4.49"	30"	14.00"	150	4.55	100'
4"	5.27"	30"	18.00"	150	5.23	100'
5"	6.45"	30"	24.00"	150	6.55	100'
6"	7.48"	30"	28.00"	150	8.9	100'
8"	9.53"	30"	48.00"	150	13.24	60'
10"	11.49"	30"	60.00"	150	15.07	40'
12"	13.74"	30"	90.00"	150	21.77	20'

Cut Lengths : Plus 10%

Standard Lengths : 3" to 6" - 100' -- 8" -60' -- 10" and 12" - 20'

Recommended Couplings : Aluminum or Ductile Split Flange



Industrial Rigging & Supply