


## SSLB - Short Span Lifting Beam (Plate Style)



### FEATURES:

- This style of lifting beam is ideal for short span applications and can be utilized where headroom is limited.
- Supplied with a pair of shackles and one standard spread.

### OPTIONS:

- Additional lift points
- Higher capacities (supplied w/upper shackle)
- Additional lengths
- Upper shackle
- Upper shackle w/oblong link
- Hooks

A - Capacity in Tons

B - Outside Spread (Feet) C

- Headroom

D - Bail Height

E - Bail Opening Width F -

Bail Opening Height G - Bail

Thickness

H - Shackle Size

I - Shackle Clearance

J - Weight (lbs)

- Engineered and manufactured to ASME B30.20 & BTH-1 Design Category B Service Class 2.

- 100% of ALL Kito Lifting Beams are Proof-Tested to 125% capacity and certificates supplied at No Additional Charge.

	A	F	B	C	D	E	G	H	I	J	
SSLB-. 25-1	1/4	1	6.9	0.63	2	4	0.5	3/8	0.9	10	
SSLB-. 25-2	1/4	2	6.9	0.63	2	4	0.5	3/8	0.9	15	
SSLB-. 25-3	1/4	3	6.9	0.63	2	4	0.5	3/8	0.9	25	
SSLB-1-1	1	1	9.6	0.88	3	3	5	5/8	1.6	20	
SSLB-1-2	1	2	9.6	0.88	3	5	0.75	5/8	1.6	40	
SSLB-1-3	1	3	9.6	0.88	3	5	0.75	5/8	1.6	50	
SSLB-3-1	3	1	10.8	1.25	3	5	1	3/4	1.8	40	
SSLB-3-2	3	2	10.8	1.25	3	5	1	3/4	1.8	60	
SSLB-3-3	3	3	10.8	1.25	3	5	1	3/4	1.8	80	
SSLB-10-2	10	2	16.1	2	4	7	1.25	7/8	2.1	110	
SSLB-10-3	10	3	16.1	2	4	7	1.25	7/8	2.1	140	
SSLB-20-2	20	2	20.1	2.5	5.5	8	1.5	1-1/4	3.1	160	

## FPSL - Four Point Sack Lifter Beam



### FEATURES

- This style of lifting beam is designed to lift bulk container sacks.
- Low headroom design that meets metric rating requirements.
- Smooth edge design to minimize wear on lifting straps.

### OPTIONS:

Additional sizes are available

	A	B	C	D	E	F	G
FPSL- 1-36SK	1	36	4.63	1	3.5	9	120
FPSL- 1-48SK	1	48	4.63	1	3.5	9	145
FPSL- 2-36SK	2	36	4.63	1	3.5	9.5	140
FPSL- 2-48SK	2	48	4.63	1	3.5	9.5	170

A - Capacity (Metric tonnes)

B - Outside Spread (Inches) C

- Headroom

D - Bail Height

E - Bail Opening Width

F - Overall Height

G - Weight (lbs)

- Engineered and manufactured to ASME B30.20 & BTH-1 Design Category B Service Class 2.

- 100% of ALL Peerless Lifting Beams are Proof-Tested to 125% capacity and certificates supplied at No Additional Charge.



Industrial Rigging & Supply

E-mail [info@industrialrigging.ca](mailto:info@industrialrigging.ca) Website - [www.industrialrigging.ca](http://www.industrialrigging.ca) Toll Free (866) 942-4774