

Hook and Shackle Snatch Blocks (Single/Double)

- Forged Alloy Heat Treated Hooks
- Forged Steel Swivel Tees, Yokes and Shackles
- Yellow Painted Head Fitting for Quick Recognition All furnished with Bronze Bushings and Grease Nipples All Blocks open for easy wire installation



Snatch Block Single Sheave with Hook

Wire size	Sheave	Qty/box	Wt. lbs	WLL 4:1
5/16"-3/8"	3"	5	5	2 ton
3/8"-1/2"	4 1/2"	4	12	4 ton
5/8"-3/4"	6"	2	27	8 ton
5/8"-3/4"	8"	1	37	8 ton



Snatch Block Single Sheave with Shackle

Wire size	Sheave	Qty/box	Wt. lbs	WLL 4:1
5/16"-3/8"	3"	5	5	2 ton
3/8"-1/2"	4 1/2"	4	12	4 ton
5/8"-3/4"	6"	2	27	8 ton
5/8"-3/4"	8"	1	37	8 ton



Snatch Block Double Sheave with Hook

Wire size	Sheave	Qty/box	Wt. lbs	WLL 4:1
3/8"-1/2"	4 1/2"	2	20	4 ton
5/8"-3/4"	6"	2	49	12 ton
5/8"-3/4"	8"	1	59	12 ton



Snatch Block Double Sheave with Shackle

Wire size	Sheave	Qty/box	Wt. lbs	WLL 4:1
3/8"-1/2"	4 1/2"	2	20	4 ton
5/8"-3/4"	6"	2	49	12 ton
5/8"-3/4"	8"	1	59	12 ton



WARNING

A potential hazard exists when lifting or dragging heavy loads with tackle block assemblies. Failure to design and use tackle block systems properly may cause a load to slip or fall, the result could be serious injury or death. A tackle block system should be rigged by a qualified person as defined by ANSI/ASME B30.



Industrial Rigging & Supply