



**Application** : For mining, construction, and industrial use :  
**Cover** Yellow cut and abrasion resistant rubber :  
**Reinforcement** Multiple layers of synthetic yarn  
**Tube** : Synthetic oil mist resistant  
**Temperature** : -35C to +80C(-30F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty
1/2"	0.91"	300	0.32	50'/100'
3/4"	1.18"	300	0.48	50'/100'
1"	1.50"	300	0.70	50'/100'
1-1/4"	1.69"	300	0.73	50'/100'
1-1/2"	1.97"	300	0.93	50'/100'
2"	2.60"	300	1.56	50'/100'
2-1/2"	3.03"	250	1.67	50'/100'
3"	3.66"	250	2.00	50'/100'
4"	4.68"	250	2.71	50'/100'

**Cut Lengths** : Plus 10%

**Standard Lengths** : 50'/100'

**Recommended Couplings** : High Pressure all sizes, mine stem and nut 1/2" - 2",  
 Universal quick acting 1/2" - 1"

## Super Service 400 Air/Water Hose



**Application** : A superior quality mining, construction and industrial hose :  
**Cover** Yellow cut and abrasion resistant rubber with blue stripe :  
**Reinforcement** Multiple layers of synthetic yarn  
**Tube** : Synthetic oil mist resistant  
**Temperature** : -35C to +80C(-30F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Qty
1/2"	0.91"	400	0.32	50'/100'
3/4"	1.26"	400	0.58	50'/100'
1"	1.50"	400	0.70	50'/100'
1-1/4"	1.85"	400	1.04	50'/100'
1-1/2"	2.09"	400	1.20	50'/100'
2"	2.60"	400	1.56	50'/100'
2-1/2"	3.11"	400	1.56	50'/100'
3"	3.74"	400	2.86	50'/100'
4"	4.72"	400	3.02	50'/100'

**Cut Lengths** : Plus 10%. No cut lengths on 2-1/2" - 3" or 4"

**Standard Lengths** : 50'/100'

**Recommended Couplings** : High Pressure all sizes, mine stem and nut 1/2" - 2",  
 Universal quick acting 1/2" - 1"



**Industrial Rigging & Supply**