



Application : Specifically manufactured to compete with OROFLEX imitation hose. This is a lightweight high pressure, extremely strong hose for general water discharge service. Ideal for rental service where long life and competitive pricing is paramount. Its compact characteristics make this an ideal hose for use with portable pumps. Especially suited for pumping oily contaminated water.

Cover Reinforcement : Black abrasion, weather and oil resistant nitrile rubber. :
 : Circular woven synthetic yarns.
Tube Temperature : Black abrasion and oil resistant nitrile rubber.
 : -20C to +80C(0F to +180F)

Nom. I.D (in)	Nom. O.D(in)	PSI	Weight (lbs)	Std Pack Qty
2	2.26	200	0.240	100'
3	3.26	150	0.350	100'
4	4.28	150	0.450	100'
6	6.30	150	0.800	100'

Cut Lengths : Plus 10%

Standard Lengths : 50'/100'

Safety Information : Not suitable for petroleum products with aromatic content over 30%.
 Not suitable for compressed air service

Recommended Couplings : Cam and groove or short shank

EPDM General Purpose Hose



Application : Air, water, agricultural spray solutions, and other dilute chemicals Excellent resistance to heat and weathering Also resists animal fats, vegetable oils. :
 Smooth red abrasion and weather resistant EPDM synthetic rubber

Cover Reinforcement : Multiple layers of synthetic yarn
Tube Temperature : Synthetic oil mist resistant EPDM synthetic rubber
 : -30C to +93C(-20F to +200F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty
1/4"	0.55"	250	0.13	300'
5/16"	0.63"	250	0.16	300'
3/8"	0.68"	150	0.15	300'
3/8"	0.67"	200	0.16	300'
3/8"	0.71"	250	0.19	300'
1/2"	0.83"	200	0.23	300'
1/2"	0.87"	250	0.27	300'
5/8"	0.98"	250	0.31	300'
3/4"	1.16"	250	0.42	300'
1"	1.42"	200	0.55	300'
1-1/4"	1.77"	150	0.62	100'
1-1/2"	2.00"	150	0.73	100'
2"	2.50"	150	1.10	100'

Cut Lengths : Plus 10%

Standard Lengths : 1/4"- 1" 50'/100'/300' reels approx, 1-1/4" - 1-1/2" 50'/100'/400'/500' reels approx, 2" 50'/100'/300' reels approx

Recommended Couplings : High Pressure 1" - 1-1/2" for air service if the working pressure exceeds 150 psi. High Pressure, Short shank, universal, or Combination nipples all other sizes.



Industrial Rigging & Supply