

TB - Telescoping Fork Truck Boom **FEATURES**



- This style of fork truck attachment is designed to efficiently lift and carry loads with a telescoping boom with locking pin allowing for multiple hook positions.
- Supplied with standard restraining chain with grab hook and attached handle for ease of boom extension.
- 12' maximum boom reach and supplied with standard swivel or fixed hooks.

OPTIONS

- Additional sizes and capacities available

Product	A	B	C	D	E	F	G	H	I	J	K	L	M
TB-30	2.5	7	22	18	1	3000	3000	2600	2200	1900	1600	1500	490
TB-40	2.5	7	22	18	1.09	4000	3200	2600	2200	1900	1600	1500	490
TB-60	2.5	7	22	18	1.36	6000	5000	4200	3500	3000	2700	2500	565
TB-80	2.5	7	22	18	1.61	8000	7000	5700	4800	4100	3600	3100	750

A - Fork Opening Height

B - Fork Opening Width

C - Fork Outside Width

D - Headroom

E - Hook Opening

F - Max Capacity at Hook Position (lbs) 3' to 6'

G - Max Capacity at Hook Position (lbs) 7'

H - Max Capacity at Hook Position (lbs) 8'

I - Max Capacity at Hook Position (lbs) 9'

J - Max Capacity at Hook Position (lbs) 10'

K - Max Capacity at Hook Position (lbs) 11'

L - Max Capacity at Hook Position (lbs) 12'

M - Unit Weight in LBS

TBP - Telescoping Pivot Fork Truck Boom

FEATURES



- This style of fork truck attachment is designed to efficiently lift and carry loads with a telescoping pivot boom with locking pin allowing for multiple hook positions.
- Supplied with standard restraining chain with grab hook and attached handle for ease of boom extension.
- 12' maximum boom reach supplied with standard swivel or fixed hooks and can pivot to a vertical height of 6'4".

OPTIONS

- Additional sizes and capacities available.

Product	A	B	C	D	E	F	G	H	I	J	K	L	M
TBP-30	2.5	7	22.5	30	1	3000	3000	2600	2200	1900	1600	1500	565
TBP-40	2.5	7	22.5	30	1.09	4000	3200	2600	2200	1900	1600	1500	565
TBP-60	2.5	7	22.5	30	1.36	6000	5000	4200	3500	3000	2700	2500	680
TBP-80	2.5	7	22.5	30	1.61	8000	7000	5700	4800	4100	3600	3100	870

100% of ALL Peerless Lifting Beams are Proof-Tested to 125% capacity and certificates supplied at No Additional Charge.

Engineered and manufactured to ASME B30.20 & BTH-1 Design Category B Service Class 2.



Industrial Rigging & Supply